(









FIG. 1
















F I G. 2C


























FIG. 4E







FIG. 4F




F I G. 5A




F I G. 5B





F I G. 5C




F I G. 5D












F I G. 7A




F I G. 7B




F I G. 7C




F1G.8A




F1G.8B




F I G. 8C





F I G. 8D





į





F I G. 8G







FIG. 9A




F I G. 9B



F I G. 9C



F I G. 9D



F I G. 9E








FIG. 9F









F I G. 11A




F I G. 11B








F I G. 12A





F I G. 12B



















\











FIG. 15B1




F I G. 15B2




F I G. 15C




F I G. 15D



F I G. 15E



F I G. 15F




F I G. 15G


$$E_{0} = \overline{(B1 + A_{0})(C_{3}/C_{1-1})}$$


$$E_{1} = (C_{3}/C_{1-2}) + B1$$


$$E_{2} = (C_{2}/C_{1})(T_{1})$$
FIG. 15H



F I G. 151







F I G. 15M

C ₃ /C ₂	A ₂	E ₃	C ₂ /C ₁
0	0	0	0
0	1	1	0
-1	х	1	1

X: DON'T CARE (I.E. C_3 / C_2 OVERRIDES A_2)

F I G. 15N

	_3	20 _32	1 _322	323	324	-325	326
P	START OF ACKET FIELD	TRANSMI TTER ID NUMBER FIELD	PACKET GROUP NUMBER FIELD	DATA PACKET NUMBER FIELD	SYMBOL CHARAC TER DATA FIELD	ERROR CODE CORREC TION FIELD	END OF PACKET FIELD

FIG. 150







FIG. 16





.)






F I G. 20A1










FIG. 20E







FIG. 21







)


J










F I G. 22B








F I G. 23A1











F.I.G. 23E







FIG. 24







F I G. 25B

j










FIG. 27B2

SYSTEM CONTROLLER CONTINUES ACTIVATION OF LASER DIODE, SCANNING MOTOR, PHOTORECEIVING CIRCUIT, A/D CONVERSION CIRCUIT; DEACTIVATES SYMBOL \mathbf{Q} DECODING MODULE; AND COMMENCES ACTIVATION OF DATA FORMAT CONVERSION MODULE AND DATA TRANSMISSION MODULE (AND/OR DATA STORAGE MODULE); DRIVE DATA TRANSMISSION STATE INDICATOR WITH E_{DT}=1 TRANSMIT SYMBOL CHARACTER DATA TO HOST DEVICE (E.G. COMPUTER, CASH REGISTER, ETC.) OR OTHER STORAGE (PROCESSING DEVICE); DRIVE DATA R TRANSMISSION STATE INDICATOR USING $E_{DT}=1$, AND DISABLE BAR CODE READ INDICATOR USING ESD=0 SYSTEM CONTROLLER DEACTIVATES DATA FORMAT CONVERSION MODULE, DATA TRANSMISSION MODULE (AND **DATA STORAGE MODULE)**

FIG. 27C







FIG. 28




\






į. J



\



F I G. 29C

$$E_{0} = \overline{(B1 + A_{0}) (C_{3}/C_{1-1})}$$

$$E_{IM} = E_{IPD} = E_{IAD} = \overline{(C_{3}/C_{1-2}) + B1}$$

$$E_{L} = \overline{(C_{3}/C_{1-1}) + B1} [B2]$$

$$E_{2} = \overline{(C_{2}/C_{1}) (B1)}$$

F I G. 29D







FIG. 30A1










FIG. 30D






FIG. 30E









FIG. 31A



F I G. 31B








FIG. 32A1
















FIG. 32E




F I G. 33A1













FIG. 33E








FIG. 34B2


SYSTEM CONTROLLER CONTINUES ACTIVATION OF LASER DIODE, SCANNING MOTOR, PHOTORECEIVING CIRCUIT, A/D CONVERSION CIRCUIT; DEACTIVATES SYMBOL Q DECODING MODULE; AND COMMENCES ACTIVATION OF DATA FORMAT CONVERSION MODULE AND DATA TRANSMISSION MODULE (AND/OR DATA STORAGE MODULE); DRIVE DATA TRANSMISSION STATE INDICATOR WITH E_{DT}=1 TRANSMIT SYMBOL CHARACTER DATA TO HOST DEVICE (E.G. COMPUTER, CASH REGISTER, ETC.) OR OTHER STORAGE (PROCESSING DEVICE); DRIVE DATA R TRANSMISSION STATE INDICATOR USING Ent=1, AND DISABLE BAR CODE READ INDICATOR USING E_{SD}=0 SYSTEM CONTROLLER DEACTIVATES DATA FORMAT CONVERSION MODULE, DATA TRANSMISSION MODULE (AND DATA STORAGE MODULE)

FIG. 34C



F I G. 35A1









FIG. 35C



F I G. 35D









FIG. 35E




















FIG. 38C




FIG. 39








FIG. 40C

FIG. 40D












F1G. 42C

· .






F16. 43F





P1G. 439




F16.43A


Retricted configuration 793 F16. 43 I 792








F16.44AZ





\




:


139/161








F16.46A1





F16 46C1



THIRD CONTROL CIRCUIT C₃ CONTINUES ACTIVATION OF LASER DIODE, SCANNING MOTOR, PHOTORECEIVING CIRCUIT, A/D CONVERSION CIRCUIT; DEACTIVATES SYMBOL DECODING MODULE; AND COMMENCES ACTIVATION DATA PACKET SYNTHESIS MODULE

· W

UNDER C₃ CONTROL, DATA PACKET SYNTHESIS MODULE CONSTRUCTS DATA PACKET CONSISTING OF SYMBOL CHARACTER DATA, TRANSMITTER NUMBER, DATA PACKET GROUP NUMBER, CHECK CHARACTER AND FRAMING CHARACTERS

IN-RF RANGE ND

IN-RF RANGE
CONFIRMATION SIGNAL

AS=1?

YES

ARE

DATA PAK KET

GLOUP(S) STORED

IN DATA PAKET

YES

C3 Content Module Economies Emplo 611=1

Reloading Buffered Data Packet Groups)

Into Data Packet Teansmission Circuit

Gunp BUFFER


AA

Control Module C3 Benerates Brake Signal E19=1 Coading Comenty Synthesizes Duta Packet Group Into Data Padlet Transmission Circuit BB

FIG. 46 CZ.

C₃ ACTIVATES DATA PACKET TRANSMISSION CIRCUIT UNDER C3 CONTROL DATA PACKET SYNTHESIS MODULE **OUTPUTS PACKETITO DATA PACKET TRANSMISSION** CIRCUIT FOR TRANSmission Base station DATA PACKET TRANSMUSION CIRCUIT Receives a preket bung become dynamit SE STATION RESERVES ALL PACKETS
EACH DATA PACKET GROUP SENT Ez control brodute generater An little beep sound (and good Read visual-indication) for each Data Packed Gump Sent To Base station Successfully

F1G. 46 C3










FIG. 47


















F1G. 47B



F16. 48 A1







THIRD CONTROL CIRCUIT C₃ CONTINUES ACTIVATION OF LASER DIODE, SCANNING MOTOR, PHOTORECEIVING CIRCUIT, A/D CONVERSION CIRCUIT; DEACTIVATES SYMBOL DECODING MODULE; AND COMMENCES ACTIVATION DATA PACKET SYNTHESIS MODULE

UNDER C₃ CONTROL DATA PACKET SYNTHESIS MODULE CONSTRUCTS DATA PACKET CONSISTING OF SYMBOL CHARACTER DATA, TRANSMITTER NUMBER, DATA PACKET GROUP NUMBER, CHECK CHARACTER AND FRAMING CHARACTERS

IN-RF RANGE
ONFIRMATION SIGNAL
AS=1?

VES

ARE
DATA PACKET
GRANGES
STREED
IN DATA PACKET
GLANG BAFFER

YES

YES

C3 Content Module Economotes Empho 511=1

Reloading Briffered Data Packet Group 8)

Into Data Packet Teamsmission Cincuit

Control Module C3 Beneautes Grable Signal E30=1 Coading Currently Synthesizes Duta facket Group Into Data Problet Transmission Ciecuit

F16.48CZ


BB

C3 ACTIVATES DATA PACKET TRANSMISSION CIRCUIT UNDER C3 CONTROL DATA PACKET SYNTHESIS MODULE **OUTPUTS PACKETSTO DATA PACKET TRANSMISSION** CIRCUIT FOR TRANSmission ase STATION DATA PARICET TRANSMUSION CIRCUIT Receives a PACKET GLOUP ACKNOWLE Agreement from BOSE STATION WHOLL SE STATION ROCCIVES ALL ARCKETS
EACH DATA PACKET GROUP SENT C3 control thodute generater
And the beep sound (and good
Read visual-indication) for each
Data Packed Gump Sent To
Base station Successfully F1G. 48C3

(8)

46

 ${f C_3}$ CONTINUES ACTIVATION OF SCANNING CIRCUIT, PHOTO-RECEIVING CIRCUIT USING ${f C_3/C_1}$ OVERRIDE; DEACTIVATES SYMBOL DECODING MODULE USING ${f E_4}$; DEACTIVATES THE DATA PACKET SYNTHESIS MODULE, DATA STORAGE UNIT, AND DATA TRANSMISSION CIRCUIT USING ${f E_5}$, ${f E_8}$ AND ${f E_7}$ RESPECTIVELY; AND DISABLES DATA TRANSMISSION STATE INDICATOR USING ${f E_0}$ =0



CONTROL MODULE ${\bf C_3}$ REACTIVATES BAR CODE PRESENCE DETECTION CIRCUIT USING ${\bf C_3/C_2}$ OVERRIDE, RESETS AND RESTARTS TIMER ${\bf T_4}$, ${\bf 0}<{\bf T_4}<{\bf 3}$ sec. AND STARTS TIMER ${\bf T_3}$, ${\bf 0}<{\bf T_3}<{\bf 5}$ sec.

(9

F1G. 48C4